

wireguard

```
traceroute www.google.de
```

```
traceroute to www.google.de (216.58.206.35), 30 hops max, 60 byte packets
```

```
14 192.178.74.165 (192.178.74.165) 29.742 ms 29.720 ms 192.178.74.163 (192.178.74.163)
    27.842 ms
```

```
15 lhr35s10-in-f3.1e100.net (216.58.206.35) 29.568 ms 29.519 ms 25.746 ms
```

```
pi@wireguard-test:~ $ netstat -rn
```

```
Kernel IP routing table
```

Destination	Gateway	Genmask	Flags	MSS	Window	irtt	Iface
0.0.0.0	192.168.10.1	0.0.0.0	UG	0 0	0		eth0
10.8.0.0	0.0.0.0	255.255.255.0	U	0 0	0		wg0
192.168.10.0	0.0.0.0	255.255.255.0	U	0 0	0		eth0

```
[Interface]
```

```
PrivateKey = 0dfgdgdgdgdgdsfgdgdsfgertfg34g34g34Z6x14=
```

```
Address = 10.8.0.6/24
```

```
DNS = 192.168.10.2
```

```
MTU = 1420
```

```
[Peer]
```

```
PublicKey = idgfgdgdgdgdgdgdgdgdgdgdgdgdgdgdgdc=
```

```
PresharedKey = 77Hh1XEDgdgfdgdgdsgdgdgfdkfaGBci2Rk=
```

```
AllowedIPs = 10.8.0.0/24. # Wichtig damit 192.168.10.X erreichbar bleibt im lokalen Netz
```

```
PersistentKeepalive = 25
```

```
Endpoint = xxxx.dnsfor.me:51820
```

Revision #3

Created 5 January 2025 15:01:03 by Joachim Hummel

Updated 5 January 2025 15:04:15 by Joachim Hummel